

This underlayment pump is easy to load and delivers batch after batch of consistently mixed material. A parabolic mixing chamber and self-measuring water tank allow the operator to accurately set the correct ratio of material for any job. The Quikspray® Underlayment Pump takes the guesswork out of application with precise operator control. Its superior mobility and high ground clearance permit access into tight areas.

At the heart of the system is a soft rubber tube fitted inside a U-shaped chamber. Peristaltic action means you never prime. Material flow can be controlled at dispensing end using a low voltage remote. With no seals, rotors or pistons, there is no danger of damage if the pump runs dry. Material touches just the hopper and the inside of the peristaltic tube, so cleanup and maintenance is quick and easy.



**15010MK-4U**

### Accessories

**L.V. Remote Control and 4.80/400-8 Wheels and 16" Pneumatic Tires**



**Automatic Water Tank for Batch Mixing**



**Hopper View with High Shear Blades**



**Custom Mixing Blades and Material End Tables**



Manufactured by:



Box 327 • Port Clinton, OH 43452

419.732.2611 • fax 419.734.2628 • [www.Quikspray.com](http://www.Quikspray.com)

Distributed by:



# UNDERLAYMENT PUMP



## Specifications

- Pumping rate up to 6 gallons 12-14 GPM
- Two 2-speed high torque mixing motors available
- Mixes and pumps continual/consistent batches
- Mixing volume controlled water tank
- Low voltage remote control for on/off
- Powered by standard 120 volt circuit
- Two 28 gallon parabolic shaped hoppers for easy mixing and flow
- Full port 1.50" stainless steel ball valves
- Long Lasting 1.50" ID peristaltic pumping Line
- Full 1.50" ID Quik couplings on material line
- Heavy-Duty steel frame
- Four large 4.80/400-8 wheels and 16" pneumatic tires
- Top mounted swing mixer for rapid mixing
- Simple easy to operate controls on the mixer and the pump

Length

- Minimum 55" (without wheels)
- Maximum 85" (with wheels and end tables)

Width

- Minimum 25" (without wheels)
- Maximum 34" (with wheels)

Height

- 41.5" (from wheels to end tables)
- 64" (from wheels to water tank)

Shipping  
Weight

- Approximately 750 lbs.



Manufactured by:

Distributed by:

Box 327 • Port Clinton, OH 43452  
419.732.2611 • fax 419.734.2628 • [www.Quikspray.com](http://www.Quikspray.com)